












MOD.	LENGHT MT	TENSION CLASS	POWER AT 60% CO2 - MIX	COOLING
BZ 15.3	3.0	L	180 A - 150 A	AIR
BZ 15.4	4.0		180 A - 150 A	
BZ 15.5	5.0		180 A - 150 A	


ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
	CE	02.ER.15.3 TORCIA COMPLETA BZ 15 mt. 3 - COMPLETE MIG TORCH BZ 15 mt. 3		
		02.ER.15.4 TORCIA COMPLETA BZ 15 mt. 4 - COMPLETE MIG TORCH BZ 15 mt. 4		
		02.ER.15.5 TORCIA COMPLETA BZ 15 mt. 5 - COMPLETE MIG TORCH BZ 15 mt. 5		
		02.ER.15.3 S TORCIA COMPLETA BZ 15 mt. 3 - COMPLETE MIG TORCH BZ 15 mt. 3 SPRING PINS		
		02.ER.15.4 S TORCIA COMPLETA BZ 15 mt. 4 - COMPLETE MIG TORCH BZ 15 mt. 4 SPRING PINS		
		02.ER.15.5 S TORCIA COMPLETA BZ 15 mt. 5 - COMPLETE MIG TORCH BZ 15 mt. 5 SPRING PINS		
	1	02.02.15ICO Ugello conico ø 12 STD - Adjustable conical nozzle ø 12 STD		10
		02.02.15ICL Ugello cilindrico - Adjustable cylindrical nozzle		10
		02.02.15.10 Ugello conico ø 9,5 - Adjustable conical nozzle ø 9,5		10
		02.02.15 IP Ugello per puntatura - Adjustable spot nozzle		10
	2	02.01.15.06 Punta guidafile ø 0,6 - Contact tip ø 0,6		100
		02.01.15.08 Punta guidafile ø 0,8 - Contact tip ø 0,8		100
		02.01.15.09 Punta guidafile ø 0,9 - Contact tip ø 0,9		100
		02.01.15.10 Punta guidafile ø 1,0 - Contact tip ø 1,0		100
		02.01.15.12 Punta guidafile ø 1,2 - Contact tip ø 1,2		100
	3	02.05.15FSX Diffusore a molla Fil. Sx (STD) - Tip adaptor gas diffuser (left thread)(STD)		
		02.05.15F Diffusore a molla (in esaurimento) - Tip adaptor gas diffuser (thread female 8 x1)(sold out)		50
	4	02.05.15.01 Molla ferma ugello gas - Spring		50
	5	02.03.15 Boccolina isolante - Insulator nut for conductor tube		
	6	02.06.15SX Lancia terminale completa Fil. Sx (STD) - Complete adjustable swan neck (left thread)(STD)		
		02.06.15I Lancia terminale completa (in esaurim.) - Complete adjustable swan neck (sold out)		
				


ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK.
	02.08.ER.16	Impugnatura ergonomica ø 16 mm.	- Ergonomic Handle with screw ø 16 mm.	
	02.08.ER.01	Vite per impugnatura	- Screw for ergonomic handle	
	02.08.ER.02	Ghiera	- Housing for handle	
	02.09.A.BZ	Pulsante interruttore STD	- Trigger STD	
	02.09.ER	Pulsante interruttore lungo	- Long trigger	

	02.144.ER.15	Supporto snodo anteriore ergonomico BZ15	- Joint for ergonomic handle BZ15	

	02.20.15.3	Cavo assemblato mt.3	- Assembled cable mt.3	
	02.20.15.4	Cavo assemblato mt.4	- Assembled cable mt.4	
	02.20.15.5	Cavo assemblato mt.5	- Assembled cable mt.5	
	VA.A22T/P	Faston Femmina	- Faston female	
	VA.B18 20	Manicotto serraggio cavi	- Sleeve	
	02.06.15.01	Dado ø 10x1 mm.	- Nut ø 10x1 mm.	
	VA.RC15E	Raccordo cavo coassiale	- Coax-cable fitting	
	01.244M	Faston interruttore	- Faston for switch	


	02.04.T3	Guaina guidafilo blu ø 0,6 - 1,0 mt.3	- Wire conduit ø 0,6 - 1,0 Blue mt.3	
	02.04.T4	Guaina guidafilo blu ø 0,6 - 1,0 mt.4	- Wire conduit ø 0,6 - 1,0 Blue mt.4	
	02.04.T5	Guaina guidafilo blu ø 0,6 - 1,0 mt.5	- Wire conduit ø 0,6 - 1,0 Blue mt.5	
	02.30.08	O-RING	- O-RING	


	02.04.AL	Guaina guidafilo per alluminio mt. 4,5	- Liner for Aluminium mt. 4,5	
	02.04.ALT	Capocorda	- Nut for liner for Aluminium	
	02.04.AL5	Guaina guidafilo per alluminio mt. 5,5	- Liner for Aluminium mt. 5,5	

	02.30.021	Supporto cavo	- Cable support	
	PL 30.03	Scatola posteriore	- Connector case	
	PL 30.04	Ghiera per BZ 15	- Nut (for BZ 15)	

	02.30.05	Corpo torcia posteriore spinette fisse	- EURO connector - FIXED PINS	
	02.30.051	Corpo torcia posteriore spinette mobili	- EURO connector - SPRING PINS	
	13.30.08	Corpo torcia Saf spinette mobili	- EURO connector Saf - SPRING PINS	
	02.30.08	O-RING	- O-RING	
	VA.A22/P	Faston maschio	- Faston male	
	02.30.06	Dado	- Liner nut	
	02.30.07	Spinetta maschio fissa	- Fixed pin	
	13.30.08.1	Spinetta maschio mobile	- Spring pin	

OPTIONALS TIPO BZ15

	02.02.15FC0	Ugello a FILETTO conico	- Theraded conical nozzle	10
	02.02.15FCL	Ugello a FILETTO cilindrico	- Theraded cylindrical nozzle	10
	02.02.15FP	Ugello a FILETTO per puntatura	- Theraded spot nozzle	10

	02.06.15FLX	Lancia flessibile ad INNESTO	- Flexible swan neck	

